

Standard Monitor ~ Touch

PT1910MX

Product Name	PT1910MX
Planar Part Number	997-3985-00 (Black), 997-3986-00 (White) ^{shown}
Viewable Size	19" diagonal (14.81" horizontal x 11.85" vertical)
Touchscreen Type	5-wire Resistive
Touchscreen Interface	Dual RS-232 Serial/USB
Transmissivity	Up to 80%
Contrast Ratio (Typical)	800:1
Viewing Angle (Typical)	160° H,V (specified at CR>10:1)
Response Time (Typical)	5 ms (3.6 ms rise, 1.4 ms fall)
Brightness (w/touchscreen)	240 cd/m ²
Display Type	LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1280 x 1024 SXGA
Palette	16.7 million colors
Pixel Pitch	0.294 mm
Refresh Rate	56 to 75 Hz
Dimensions	17.2" x 14.6" x 2.7" (438.0 mm x 370.8 mm x 68.6 mm)
Display Weight	19.6 lbs (8.9 kg) (net), 25.8 lbs (11.7 kg) (shipping)
Display Weight	14.1 lbs (6.4 kg)
Panel Depth	2.7"
Display Weight	14.04 lbs (6.37 kg) net, 16.36 lbs (7.42 kg) shipping
Video Inputs	Digital (DVI-D), Analog
Audio Output	2 speakers, 1W/ch
External Connections	D-sub 15-pin, D-sub 9-pin, DC power connector, Type B socket USB, Stereo jack - 3 mm
Compatibility	Windows® Vista, XP, XP Embedded, CE, 2000, ME, 98; Linux; Apple® Mac OS
Power Supply	12V DC power connector
Power Consumption	50W
VESA Compatible / Location	Built-in 75mm and 100mm VESA, back
Options / Features	Anti-glare coating, Multi-language support, On screen display



Standard Monitor

→ PQ1910M ←

Product Name	PQ1910M
Planar Part Number	997-3188-00 (Black)
Viewable Size	19" diagonal (14.81" horizontal x 11.85" vertical)
Contrast Ratio (Typical)	800:1
Viewing Angle (Typical)	160° H,V (specified at CR>10:1)
Response Time (Typical)	5 ms
Brightness (Typical)	300 cd/m ²
Display Type	LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1280 x 1024 SXGA
Tilt Range	-5° to +40°
Palette	16.7 million colors
Pixel Pitch	0.294 mm
Refresh Rate	60 to 75 Hz
Dimensions	16.65" x 13.98" x 1.97" (423 mm x 355 mm x 50 mm)
Panel Depth	1.97"
Display Weight	14.04 lbs (6.37 kg) net, 16.36 lbs (7.42 kg) shipping
Video Inputs	Digital (DVI-D), Analog
Audio Output	Integrated TrueMedia™ 2W/channel stereo speakers
External Connections	Qty (1) DVI 24-pin connector, Qty (1) VGA D-sub 15-pin video connector, Qty (1) 1/8 inch audio jack
Compatibility	PC
Power Supply	12V DC power connector
Power Consumption	45W (2W standby)
VESA Compatible / Location	Built-in 75 mm VESA, monitor back
Product Approvals	FCC-B, UL/cUL, CE, WEEE, Rohs
Options / Features	Slim bezel design, VESA DPMS compliant, EPA Energy Star, Plug & Play VESA DDC1/2B, 75 mm VESA standard built-in (located on the back of monitor), 2W/channel stereo speakers

